









Technical data	Characteristics	Standards	Unit	DELTA	
<h2>Extra XL</h2> <p>Marbleised, directional vinyl sheet flooring with a polyurethane surface treatment.</p>         <p>100 % RECYCLABLE 25 % RECYCLED MATERIAL</p>  <p>This product has been independently tested and results demonstrate that it does not favour the growth of MRSA on the flooring. An effective cleaning regime is however, the most important defence against infection.</p>	Type of floorcovering	EN 649 EN ISO 10581		homogeneous, PVC	
	Surface treatment			PUR	
	Description				directional, marbleised
	Colours				12
	Special characteristics				–
	Total weight	EN 430 EN ISO 23997	g/m ²	3.200	
	Performance classification	EN 685 EN ISO 10874		23, 34, 43	
	Gauge	EN 428 EN ISO 24346	mm	2,0	
	Packaging roll size	EN 426 EN ISO 24341	m / m ²	2 m x 20 m / 40 m ²	
	Packaging tile size	EN 427 EN ISO 24342	mm / m ²	–	
	Residual indentation	EN 433 EN ISO 24343-1	mm	≤ 0,1	
	Colour fastness to artificial light	EN ISO 105-B02 method A	level	≥ 6	
	Behaviour to fire	EN 13501-1		B _{fl} - s1	
	Slip resistance	DIN 51130 EN 13893		R9 DS	
	Impact sound reduction	EN 140-8 EN ISO 10140-3	dB	2	
	Resistance to thermal conductivity	EN 12667 ISO 8302	m ² k/w	0,02	
	Electrostatic properties when walked on	EN 1815	kV	< 2	
	Electrical resistance to earth	EN 1081	Ohm	–	
	Chemical resistance	EN 423 EN ISO 26987		*	
	Abrasion group	EN 660-2 EN ISO 10581		M type II	
Castor chair suitability	EN 425 ISO 4918		yes, type W, EN 12 529		
Underfloor heating suitability	EN 1264-2		suitable, max. 27 °C		
AgBB VOC test			very low emission		
* Resistant depending on concentration and time of exposure, in case of increased impact of oils, grease, acids, alkalis and other aggressive chemicals — please contact us.					